



BOILER SYSTEMS SINCE 1946

RFWS-300AB Feedwater System For Use With RB-300A&B



Complete feedwater system for upto 600HP (20,700 PPH). Feedwater tank is equipped with two pumps each sized for 300HP. All components are shipped loose for field installation and must be protected from the elements.

INCLUDES:

750 Gallon Feedwater Tank:

- Level control
- Sight glass assy.
- Duplex pumps (1 per boiler)
- Chemical injection quills with metering Pumps

Connection Sizes:

- Soft water inlet: 1" NPT
- Condensate return: 2-1/2" NPT
- Vent: 4" NPT
- Pump outlet x2: 1-1/4" NPT

Electrical Requirements:

- 460v 60hz 3-phase, 100AMP

Dimensions: 114" L x 52" W x 102" H

Weight: 2400 lbs

RB-300AB
300HP, 900 PSIG Vapor Steam Generators



Duplex Water Softening System:

- (2) Tank system - one in operation, one in standby for continuous soft water
- 300K Grain capacity based on 10 grain setting
- Brine tank

Connection Sizes:

- Feedwater: 2" NPT

Dimensions: 48" x 72" x 72"

Weight: 1130 lbs

Duplex Blowdown System:

- Capacity for (2) 300HP boilers
- After cooler

Connection Sizes:

- Blowdown: 2" 600# Flanged
- Aftercooler: 2" 150# Flanged
- Drain: 8" 150# Flanged
- Vent: 12" 600# Flanged

Dimensions: 134" H x 30" W

Weight: 1920 lbs