

# RT-1.5HW

1.5MMBTU

POTABLE/PROCESS
HOT WATER RENTAL

# EQUIPMENT SPEC SHEET

IN MANY JURISDICTIONS, THE USE OF A PRESSURIZED BOILER OR A HYDRONIC HEATER WITH A RATING OF OVER 1 MILLION BTU RESULTS IN INCREASED PERMITTING, INSPECTIONS AND STAFF WITH BOILER TICKETS. USING A NON-PRESSURIZED WATER HEATER SYSTEM, WITH TWO 900,000 BTU BURNERS IN THE 1800 HYDRO HEAT PRO, MINIMIZES THESE OVERHEAD COSTS AND THE TIMELINE, SIGNIFICANTLY INFLUENCING THE SUCCESS OF YOUR HEATING PROJECT.

#### DIMENSIONS:

L 212" x W 93.5" x H 114"

**WEIGHT.....**9,000 LBS (ESTIMATE)

BURNER.....TWO STAGE

#### FUEL SPECS:

#### DIESEL

INPUT CAPACITY

1,792,000 BTU/H

OUTPUT CAPACITY

1,523,000 Вти/н

CONSUMPTION (MAX)

12.8 US GPH

#### NATURAL GAS

INPUT CAPACITY

1,690,000 Вти/н

OUTPUT CAPACITY

1,352,000 Вти/н

CONSUMPTION (MAX)

1,577 CU FT/H

# PROPANE

INPUT CAPACITY

1,715,000 Вти/н

OUTPUT CAPACITY

1,372,000 Вти/н

CONSUMPTION (MAX)

18.7 US GPH

#### WATER HEATER:

WATER JACKET/FIRE TUBE TYPE

#### FLUID TEMPERATURE RANGE

130F to 180F

# CONTROLS AND MONITORING:

PUMP AND TEMPERATURE CONTROLS, FULL GAUGE PANEL SHOWING CIRCULATION FLUID TEMPERATURES AND PRESSURES, 7-LIGHT SYSTEM OPERATION FEATURE FOR EASY TROUBLESHOOTING

#### WATER HEATER CIRCULATION PUMP:

3 HP, 110 US GPM @ 30 PSI

#### ELECTRICAL

230 V, SINGLE PHASE, 60 Hz, 2 x 30 A (L14-30)

#### INTERNAL FLUID CIRCULATION SYSTEM:

#### BASIC FEATURES

ATMOSPHERICALLY VENTED LOW PRESSURE SYSTEM WITH A SINGLE SUPPLY AND RETURN, ADJUSTABLE FLUID TEMPERATURE CONTROL, AUTO PRESSURE BY-PASS FOR PUMP PROTECTION AND VARIABLE FLOW DEMANDS, AUTO TEMPERATURE BYPASS FOR HEAT EXCHANGER PROTECTION

#### PLATE HEAT EXCHANGERS:

2 MILLION BTU, SERVICEABLE, QUANTITY 2, ONE FOR POTABLE AND ONE FOR PROCESS WATER

#### PLATE HEAT EXCHANGER PUMPS:

3 нр, 110 US GPM @ 30 PSI,

QUANTITY 2

## CONTAMINATION PROTECTION:

PRE-SCREENING PRIOR TO THE PLATE HEAT EXCHANGERS

Quick connect couplers:  $2^{"}$  Kamlok $^{\circledR}$  couplers

### **HEAT TRANSFER FLUID (HTF):**

NON-TOXIC PROPYLENE GLYCOL/WATER MIXTURE

# LOADING (STANDARD):

FORKLIFT POCKETS

#### LOADING (OPTIONAL):

BOLT ON LIFTING FRAME

#### **CERTIFICATION:**

CSA/UL CERTIFIED

